BAILEY METAL PRODUCTS STRUCTURAL STEEL THICKNESSES





GAUGE	THICKNESS (INCH)	THICKNESS (mm)	COLOUR
20	.033"	0.84	White
18	.043"	1.09	Yellow
16	.054"	1.37	Green
14	.068"	1.73	Orange
12	.097"	2.46	Red

Structural studs must have a minimum protective coating of G60. All Bailey structural studs are G60. Structural studs must have a minimum steel thickness (base steel) of no less than 0.033 inches. All Bailey studs have a base metal thickness greater than 0.033 inches.



sales@bmp-group.com

www.bmp-group.com







STRUCTURAL PRODUCT IDENTIFICATION

The cold-formed steel framing manufacturers use a universal designator system for their products.

The designator is a four part code which identifies depth, flange width, member type and material thickness.



EXAMPLE: 600S162-54

Member depth in 1/100ths inches. Thus 600 means 600/100 = 6"

600 S

Style: S = Stud or joist sections

T = Track sections

U = Channel sections

F = Furring channel sections

Flange width in 1/100ths inches.
Thus 162 means 162/100 = 1.62" or 1 5/8"

162 - 54

Material thickness in 1/1000ths inches. Thus 54 means 54/1000 = 0.054"

Notes:

- Material thickness is given as the minimum thickness exclusive of coatings and represents 95% of the design thickness. See CAN/CSA S136-12 North American specification for the design of cold-formed steel structural members.
- 2. For those sections available in two different yield strengths, the yield strength used in the design, if greater than 33 ksi, needs to be identified (i.e., 600S162-54 (50 ksi)). In any case, it is good practice to always show the yield strength and eliminate any potential ambiguity.
- 3. For track, "T" sections, member depth is a nominal inside to inside dimension plus one inside radius. Other dimensions are out to out.
- 4 This product designation method is also known as "STUF" nomenclature.
- 5. This product labelling is independent of units. For example 600S162-54 (50 ksi) applies whether imperial or metric units are used.



C-STUD / JOIST

S-SECTIONS

TRACK

T-SECTIONS



CHANNEL

U-SECTIONS



FURRING CHANNELS

F-SECTIONS

sales@bmp-group.com

www.bmp-group.com





