


EXTENDED FAST CLIP™

PROVIDES FOR VERTICAL BUILDING MOVEMENT UP TO 3" AND IS COMMONLY USED FOR LARGE STANDOFF CONDITIONS

EXTENDED FastClip™ (FCEC) 68mils (14ga) deflection clips (8" clip is available in 14ga & 12ga) are used to attach exterior curtain wall studs to the building structure and provide for vertical building movement independent of the cold-formed steel framing.

The clips are available in standard lengths of 6", 8", 10" and 12" and are ideal for medium to larger standoff conditions. EXTENDED FastClip™ deflection clips install quickly with screws, welds or powder-actuated fasteners, and provide adjustable standoff to ensure a plumb wall plane. FastClip™ Deflection Screws are provided with each clip to ensure friction-free sliding.

- Eliminates shims and scabs.
- Vertical movement up to 3" (1-1/2" up and 1-1/2"down).
- Specially designed to simplify welding installation
- Fast, one-piece universal installation. No left or right handed clips
- FastClip™ Deflection Screws (included) provide frictionless slip connections
- · Custom and longer lengths available
- U.S. Patent No. 6,688,069





FastClip™ 14GA system meets Intertek CCRR-0208 in compliance with the 2018, 2015 & 2012 International Building Code® (IBC) and International Residential Code® (IRC), as well as the 2017 Florida Building Code and 2016 California Building Code.

Meets SFIA Certification for Manufacturing Compliance Program for Connectors for Cold-Formed Steel Construction.

PRODUCT DATA & ORDERING INFORMATION

Product code	Gauge	Mils	Design thickness (in)	Size (in)	Pcs./Bucket
CLIP-FCECX6	14	68	0.0713	1-7/8" x 6" x 4-3/4"	25
CLIP-FCECX8	14	68	0.0713	1-7/8" x 8" x 4-3/4"	25
CLIP-FCECX8-97	12	97	0.1017	1-7/8" x 8" x 4-3/4"	25
CLIP-FCECX10	14	68	0.0713	1-7/8" x 10" x 4-3/4"	25
CLIP-FCECX12	14	68	0.0713	1-7/8" x 12" x 4-3/4"	25

Includes 80 FastClip deflection screws per box Material Structural Grade 50 Type H (ST50H), 50ksi Coating G90 (Z275) hot-dipped galvanized coating

