



Extended Uni Clip™ (UXRC)



Extended Uni Clip™ (UXRC) Installation

## 14 GAUGE RIGID CONNECTION CLIP

Extended Uni-Clip™ rigid framing clip is used to attach exterior wall studs to the structure of the building.

Designed to transfer horizontal and vertical loads, the extended rigid clips installs easily with screws, powder-actuated fasteners, or welds. This clip is ideal for all medium and large standoff conditions.

### PRODUCT DATA & ORDERING INFORMATION

Product code	Gauge	Mils	Design Thickness (in)	Size (in)	Packaging Pcs./ Ctn
CLIP-UXRC8	14	68	0.0713	1-7/8 x 4-7/8 x 8	25

Material Structural Grade 50 Type H (ST50H), 50ksi  
Coating G90 (Z275) hot-dipped galvanized coating  
See submittals for product weights

### INSTALLATION

Attach the Extended Uni-Clip rigid clips to cold-formed steel framing members using #12 minimum self-drilling screws driven through the clip holes into the steel framing. Follow the required fastener placement patterns to achieve the allowable load. Connections to the primary building frame can also be made with powder-actuated fasteners or welds per design requirement.

\* Extended Uni Clip™ (UXRC) are distributed by Bailey Metal Products in Canada under permission granted by ClarkDietrich Building Systems. ClarkDietrich Extended Uni Clip™ (UXRC) is a trademark of ClarkDietrich.