

FASTBRIDGE™

(FB33, FB43 & FB68)

USED TO SECURE U-CHANNEL TO WALL STUDS FOR LATERAL BRACING

The **FastBridge clip** is used to secure u-channel to structural or non-structural wall studs when used in load-bearing, curtain wall or drywall framing applications.

The wall stud friction fit design allows for as little as one screw for the connection to the U-Channel.

The **FastBridge clip** is a stiffened, G90 galvanized steel clip that's tested and designed to facilitate the rapid, efficient installation of 1-1/2" U-Channel lateral bracing for exterior curtain wall framing, loadbearing walls or interior partitions constructed of structural or non-structural studs.

U.S. Patent No. D692,746 - Canadian Patent No. 152,547

The **FastBridge clip** is available in three versions:

- **(FB33) 20-gauge light-duty clip**
For use with 20-16 gauge structural studs
- **(FB43) 18-gauge light-duty clip**
For use with 20-16 gauge structural studs
- **(FB68) 14-gauge heavy-duty clip**
For use with 16-12 gauge structural studs



FastBridge™



FastBridge™ Installation

PRODUCT DATA & ORDERING INFORMATION

Product code	Mils	Gauge	Yield Strength	Design thickness (in)	Min. thickness (in)	Knockout Size	Packaging pcs./ bucket
CLIP-FB33	33	20 STR	33ksi	0.0346	0.0329	1-1/2"	200
CLIP-FB43	43	18	33ksi	0.0451	0.0428	1-1/2"	200
CLIP-FB68	68	14	50ksi	0.0713	0.0677	1-1/2"	200

Coating: G90