

# **PRODUCT DATA SHEET**





# GABLE/RAKE FLASHINGS - EAST

90°

Rake/Gable Flashings are used along the gable edge of a roof to protect it from water penetration and to protect the fascia from water damage and staining. During severe winds, shingles are more likely to lift along the rake edges where they don't have the benefit of shingle overlap at the edge.

#### **PRODUCT INFORMATION**

Product Code:	GRFL3007515X120 / GRFL3007515X120	Product Weight:	8' – 1.68 lbs / 10' - 2.10 lbs
Dimensions:	2-3/8" × <sup>3</sup> /4"	Coating:	Zinc (galvanization) & Paint
Stock Length:	8' & 10'	Nominal Thickness:	.015" mils
Packaging:	300 per lift		

# ASTM & CODE STANDARDS

Galvanized materials and coatings are to the requirements of ASTM A653 / A653M, "Steel sheet, Zinc-Coated (Galvanized) or Zinc-Iron-Alloy-Coated (Galvannealed) by the Hot Dip process."

## LEED INFORMATION

At **BAILEY METAL PRODUCTS** we are committed to the advancement of environmentally friendly green building products that reduces energy consumption and waste. LEED MR c-4, MR c-5, MR-c2.2.

Correct at time of publishing (May 2019)

## **RELATED DOCUMENTS**

1. Roofing East (Feature Sheet)

Visit https://www.bmp-group.com/ products/roofing-products for documents.

