

BAILEY ADJUSTABLE SIDE MOUNT **BRICK CONNECTOR** 



**BAILEY METAL PRODUCTS LIMITED** has developed a versatile side mount brick connector system.


The new side mount system consists of a stainless steel tie plate, plastic thermal break/ positioning tab, and a stainless steel v-wire.

This system provides strength, corrosionresistance, adjustability, and positive placement while solving issues of dissimilar metals and thermal transfer. One size really does fit all as the new Bailey stainless steel tie plate accommodates a range of sheathing thicknesses.

Performance tested, the BAILEY ADJUSTABLE **SIDE MOUNT BRICK CONNECTOR** meets or exceeds all relevant building codes and standards. (Patent Pending)

## **DESIGNED TO MEET/EXCEED INDUSTRY STANDARDS NEXT DAY DELIVERY • INNOVATIVE**










sales@bmp-group.com

www.bmp-group.com



# **BAILEY SIDE MOUNT BRICK CONNECTORS**



### Performance:

- In tests, the new Bailey Side Mount Brick Connector limits any free play to significantly below the CSA standard of up to 1.2mm
- · Provides protection against dissimilar metals
- The plastic positioning tab also protects against thermal transfer
- The positioning tabs also control the depth position in the cavity space and prevents any interference with the brick application
- Plastic positioning tab ensures proper installation providing consistent horizontal alignment (misalignment will reduce performance significantly)
- · Adjustable brick tie accommodates a wide range of sheathing thicknesses (0.5", 1", 1.5", 2") & (2.5", 3", 3.5", 4")
- ESS connectors are manufactured from 50 ksi minimum yield strength steel
- · For severe environments, as identified by the masonry requirements of CSA A370, Bailey ESS connectors provide the ultimate durability
- Engineered to CSA A370 and ASTM A666, ASTM A580 standards

#### **Designs:**

- The Bailey design incorporates unique features that will prevent common installation problems
- The positioning tabs eliminate misalignment difficulties and provides the required control for the depth positioning of the connector plate into the wall cavity
- The plastic positioning component optimizes the thermal performance of the new Bailey brick connector system
- It also provides separation between the tie plate and the screws which solves the issue of galvanic corrosion
- Adjustable brick tie accommodates a wide range of sheathing thicknesses
- The side mount connector is manufactured from 16 gauge stainless steel (1.367 mm, 0.054") minimum base steel thickness
- · Plastic Thermal Break
- The thermal break is manufactured from polyethylene. The plastic separator fits over the side mount connector and provides a thermal separator, solves the issue of "dissimilar metals", and facilitates perfect horizontal alignment

ITEM	Mechanical Free Play	Serviceability at 0.45 kN (100 lbs)		Factored Resistance
UNIVERSAL SM/WP 3" Stainless	0.406 mm	Tie mounted directly to durable surface		2.406 kN
4.75" 6.75"	max. (0.016")	Deflection	Deflection + Free Play	(541 lbs.)
3"		0.634 mm (0.025")	1.040 mm max. (0.041")	

NOTES: \* The data reported is based on connector testing in accordance with CSA A370, Connectors for Masonry.

\* Both compression and tension capacities of the Side Mount Universal Connector were tested with the governing values listed.

\* The factored resistance value does not consider fastener resistance. A compatible fastener with adequate factored resistance is recommended.

#### **Economics:**

- The new Bailey Side Mount Brick Connector design provides a combination of superior performance and economics
- The new side mounted design, stocked in both sizes, will accommodate 90% of projects
- Packaged together with the plastic separator (125 per box)
- The Adjustable Side Mount Connectors are compatible with all Bailey steel framing systems

Please note #12 x 3/4 Hex Washer Head Screws with Bonded EPDM Washers are available from Bailey packaged 250 per box.









sales@bmp-group.com

www.bmp-group.com

